

Gledhill now offers a plow and hitch for most 1-ton and 1-1/2 ton series trucks. The Husky is 32" high and is available in three (3) different lengths: 8', 8-1/2' and 9'. Heavy duty construction can be found throughout the plow and the quick pin hitch. The "X" bracing on the moldboard provides extra strength for municipal applications. The top curvature of the plow is rolled forward to help deflect snow down and away from the windshield, greatly improving vision and safety. The Husky is hydraulically reversible. Computer designed and road proven, the Husky plow has the strength to push on!



SPECIFICATIONS

HuskyTM Plows

Power Reversible HuskyTM Plows

PLOW MODEL	PLOW LENGTH	PLOW HEIGHT	TRIP SPRINGS	CUTTING SWATH @ 35°	MOLDBOARD OVERHANG	WEIGHT APPROX.
HUSKY 8'	8'	32"	2	78"	18"	750#
HUSKY 8-1/2'	8-1/2'	32"	2	83"	18"	770#
HUSKY 9'	9'	32"	2	88"	18"	790#

All Husky plows come standard with #12 Gauge Moldboard, Push Tube, A-Frame, Open Extension Trip Springs, Cushion Valve, Built-in-Baffle, 1/2" x 6" Cutting Edge, Lift Chain, 2" x 12" S.A. Reversing Cylinders, Cylinder Pins, Plow Hoses, Fittings, Quick Disconnects and Plow Markers. Paint colors available: Blue, Red, Orange, Yellow, Black. Options Available: #10 Gauge Moldboard, Carrying Device, Tapered Moldboard.







Husky Custom Hitch

The Husky Hitch Model 450 is custom-built for your specific model truck. The Husky custom hitch provides unparalleled strength and reliability with 3/4" thick push arms and 3" x 2" boxed cross member. Easily detached from the truck by removing (2) pins, all that remains for summer operation are the (2) connecting "pockets". Hitch includes a 2-1/2" x 6" double acting lift cylinder. A snowplow light bracket is conveniently built into the hitch assembly, to allow for easy installation of snowplow lights (lights sold separately).

Call Gledhill or your Gledhill dealer to find out if the Husky Plow & Hitch are right for your year, make, & model of truck!

The Gledhill Road Machinery Co.

www.gledhillonline.com

P.O. Box 567 • Galion, Ohio 44833 phone: 419-468-4400 • fax: 419-468-6621



Scan the QR code
with your
smartphone
to visit our website.