

TECHNICAL SPECIFICATIONS

2300 SPECIFICATIONS

STEEL BLADES	Blade Width	90"	96"	104"	
	Plowing Width at Full Angle	78"	85"	93"	
	Blade Height	27.5"	30"	30"	
	Blade Material	11 Gauge Steel	11 Gauge Steel	11 Gauge Steel	
	Cutting Edge	3/8" X 6" Top Punched	1/2" X 6" Top Punched	1/2" X 6" Top Punched	
	Average Weight Complete ¹	740 lb	770 lb	810 lb	
POLY BLADES	Blade Width	90"	96"	102"	108"
	Plowing Width at Full Angle	78"	85"	90"	96"
	Blade Height	29"	29"	29"	29"
	Blade Material	HD Poly with UV Stabilizer	HD Poly with UV Stabilizer	HD Poly with UV Stabilizer	HD Poly with UV Stabilizer
	Cutting Edge	1/2" X 6" Top Punched	1/2" X 6" Top Punched	1/2" X 6" Top Punched	1/2" X 6" Top Punched
	Average Weight Complete ¹	795 lb	820 lb	840 lb	860 lb

¹ Actual weight varies with vehicle mounting

2500 SPECIFICATIONS

POLY BLADES	Blade Width	90"	96"	102"	108"
	Plowing Width at Full Angle	78"	85"	90"	96"
	Blade Height	29"	29"	29"	29"
	Blade Material	HD Poly with UV Stabilizer	HD Poly with UV Stabilizer	HD Poly with UV Stabilizer	HD Poly with UV Stabilizer
	Cutting Edge	1/2" X 6" Top Punched	1/2" X 6" Top Punched	1/2" X 6" Top Punched	1/2" X 6" Top Punched
	Average Weight Complete ¹	801 lb	824 lb	844 lb	865 lb
STEEL BLADES	Blade Width	90"	96"	104"	
	Plowing Width at Full Angle	78"	85"	93"	
	Blade Height	29"	29"	30"	
	Blade Material	11 Gauge Steel	11 Gauge Steel	11 Gauge Steel	
	Cutting Edge	3/8" X 6" Top Punched	1/2" X 6" Top Punched	1/2" X 6" Top Punched	
	Average Weight Complete ¹	745 lb	775 lb	815 lb	

¹ Actual weight varies with vehicle mounting

2500V SPECIFICATIONS

SERIES 2500 V	Blade Width	96"
	Plowing Width at Full Angle	83"
	Blade Height	29"
	Blade Material	HD Poly with UV Stabilizer
	Cutting Edge	1/2" X 6" Center Punched
	Trip Action	Trip Edge
	Angle Cylinders	2.25" X 9" Double Acting ²
	Lift Cylinder	2" X 6"
	Mounting Type	One Piece Removable
	Average Weight Complete ¹	998 lb

¹ Actual weight varies with vehicle mounting

² Cylinders use 2.25" piston with 1.5" shaft.