# Source One Supply, Inc.

# **HEATED LED SNOW PLOW HEADLIGHT** LOW/HIGH BEAM + PARKING + TURN SIGNAL + SIDE MARKER + CORNER LOW BEAM



# Full road illumination without dark corners

- Compliance: DOT FMVSS108 | SAE J914 | SAE J588 | SAE J222
- Color Temperature 5700k •
- Service life approximately 30,000 hours ٠
- Housing: Aluminum alloy | Lens: Anti-UV PC + Hardening Process
  Operating voltage 10 to 30 VDC
- Full road illumination without dark corners
- IP66 / IP69K rating
- 2 year warranty.





www.sourceonesupply.com

Low Beam + Auxiliary

sales@sourceonesupply.com

Parking

Turn Signal + Side Marker


844-539-4677

# HEATED LED SNOW PLOW HEADLIGHT LOW/HIGH BEAM + PARKING + TURN SIGNAL + SIDE MARKER + CORNER LOW BEAM









Dimensions in mm



## **Functions, Standards/Approvals**

P/N: RE7107S1S

**Functions**: **De-icing.** Low Beam, Corner Low Beam, High Beam, Turn Signal, Side Marker, Parking **Approvals**: DOT FMVSS108/SAE J914/SAE J588/SAE J222/ECE R112, R6, R7, R10

**Optical and Electrical Features** 

LED Type: OSRAM

Color Temp: 5700K

**Energy Consumption** (tested): Low Beam 30W; High Beam 21W; Corner Low Beam 11W; Turn Signal 2W; Parking 0.5W

Current Draw @ 12V (tested): Low Beam 2.5A; High Beam 1.75A; Corner Low Beam 0.92A;

Turn Signal 0.17A; Parking Light 0.04A

### **De-icing Features**

De-Icing Technology: Patented replaceable modular

De-icing Power: 55W

Control Mode: Automatic temperature sensor activates @ <41° F

**Electromagnetic Features** 

EMC Grade: CISPR 25 Class 3

Operating Voltage: 10 to 30 VDC

Decoder: PWM

Connector: 6 pin Deutsch connector

## **Mechanical Features**

Size: 230X164X116mm

Housing Material: Aluminum Alloy

Lens Material: Anti-UV PC + Hardening Process

PC Brand: COVESTRO 2407

Bracket Material: 304 Stainless Steel

Anti-Corrosion: ISO 9227 240H

Vibration Level: 15.3Grm

IP Rating: IP66, IP69K

Work Temp: -40 to +50°F

Life Time: >30,000h



www.sourceonesupply.com

sales@sourceonesupply.com

844-539-4677